SAFEST WORLD S.R.L.

TECHNICAL SPECIFICATIONS

ANTI-TERRORISM SELF-PROPELLED ROAD BARRIER

CENTURION

SIZE: 2600 X 1600 H 1000 mm

'H' MAIN STRUCTUREIN HIGH RESISTANCE STEEL: 2200 X 1200 H 950 mm

REINFORCED CONCRETE BLOCKS: n34

STANDARD EXTERNAL CLADDING: CONCRETE

CUSTOMIZED EXTERNAL CLADDING: WPC, WOOD, STONE, CORTEN, MARBLE

STANDARD ARRANGEMENT: PLANTER

CUSTOMIZED ARRANGEMENT: INFORMATION TOTEM, FOUNTAIN, ADVERTISING BANNER

LIFT: 400 mm

MAX SPEED: 2KM/H WEIGHT: 2500 kg

TRACKED UNDERCARRIAGE CF30: RUBBER TRACKS

UNDERCARRIAGE POWER SUPPLY: ELECTRIC

CAMERAS: n2

PROXIMITY SENSORS

ARMORED WIFI UP CONTROL WITH ALPHANUMERIC CODE

REMOTE CONTROL TRANSFER TO OPERATIONS CENTRE UPON REQUEST

BATTERIES: 12V X 220AH n12

OPERATING TIME: 2 HOURS OF CONTINUOUS WORK

STAND BY: 24DAYS

CHARGING SYSTEM WITH DOCK SOCKET 220 Volt

PATENT APPLICATION OCTOBER, 6TH, 2017 n° 102017000112678

ANTI-TERRORISM CERTIFICATE PENDING:

STANDARD ASTM F2656-15-C7 BSI PAS68:2013 V/7500(N3) IWA 14-1:2013 V/7200(N3C)

